

### **Emergent Collection**

Proudly manufactured in America, Emergent LVT celebrates the vibrant, versatile spirit of our local communities. Appealing natural wood visuals are designed to fit any interior, providing a core collection of LVT styles to use for a variety of projects.

#### **Features**

- Diverse color line from traditional woods to contemporary grey tones with rustic flair
- 6" x 48" nominal Plank size

938 Canyon

- 20 mil wear layer protected with M-Force™ 1 Enhanced Urethane Finish
- 4.5mm (floating) & 2.5mm (Glue Down) overall thickness
- Locking System keeps planks tightly in place and saves on adhesive cost

- No-polish maintenance reduces costs
- Optional underlayments include Mohawk AccuSound™ (glue), and ActiveSound™ (floating)
- Primary adhesive is Mohawk M700
- FloorScore® Certified
- Limited 10 Year Commercial Warranty
- Limited 25 Year Residential Warranty



949 Iron Gate

958 Garden Wall

### Town Center II

Town Center II offers an array of beautiful colors from soft, warm neutrals to bold, vivid accents. Available in our Weldlok® broadloom backing system and is available in both a 30 oz. and 36 oz. weight.





# COLORSTRAND®

### PERFORMANCE & DESIGN

- Wide variety of colors for excellent design flexibility
- Unsurpassed colorfastness to light and to atmospheric contaminants
- Excellent durability and longevity of color
- Resistant to harsh cleaning agents
- Mohawk Protection Plus Soil & Stain Resistant Technology

### **SUSTAINABILITY**


- Contains an average of 40% pre-consumer recycled content
- CRI Green Label Plus® certified

#### WARRANTY

- Lifetime Limited Wear Warranty
- Lifetime Static Warranty
- Lifetime Limited Colorfastness To Light Warranty
- 10 Year Limited Colorfastness To Atmospheric Contaminants Warranty
- 10 Year Limited Stain Resistance Warranty

### Weldlok® Plus

Weldlok® Plus is an advanced high performance backing system designed to provide long term carpet durability while delivering sustainable benefits. The backing system utilizes a high performance thermoset adhesive designed to deliver greater dimensional stability and long term performance by encapsulating the carpet back stitch, and securing the secondary backing to the substrate. Weldlok® Plus contains a minimum of 31% pre-consumer recycle content by total product weight.



### **PERFORMANCE**

- High performance backing designed for demanding commercial environments
- Greater dimensional stability no growing or shrinking
- High tuft bind properties
- Eliminates edge ravel and zippering

### INSTALLATION

• Direct glue or stretch in installations

### SUSTAINABILITY

- Minimum 31% pre-consumer recycled content by total product weight
- NSF / ANSI 140 Gold Certified
- CRI Green Label Plus Certified

### **WARRANTY**

Lifetime Limited Tuft Bind, Edge Ravel,
 Zippering, Delamination and Dimensional
 Stability Warranty

## **Specifications**

BROADLOOM &	Gauge	Define Broadloom Denote / 2B125 Tufted Level Multi-Colored Patterned Loop 1/12" (47.00 rows per 10 cm) 69% Solution Dyed / 31% Yarn Dyed Colorstrand® Nylon Mohawk Protection Plus Stain Mohawk Protection Plus Soil Woven Polypropylene Weldlok® Plus Green Label Plus Certified # 3802 Gold 12" width (3.66 m) 0.6" W x 1.0" L ASTM E 648 Class 1 (Glue Down) ASTM E 662 Less than 450 AATCC-134 Under 3.5 KV Lifetime Limited Wear Warranty Lifetime Limited Edge Ravel, Zippering, Delamination and Dimensional Stability Warranty Lifetime Limited Colorfastness to Light Warranty 10 Year Limited Stain Resistance Warranty		Gauge	Define Broadloom Construe / 2B126 Tufted Level Multi-Colored Patterned Loop 1/12" (47.00 rows per 10 cm) 68% Solution Dyed / 32% Yarn Dyed Colorstrand® Nylon Mohawk Protection Plus Stain Mohawk Protection Plus Soil Woven Polypropylene Weldlok® Plus Green Label Plus Certified # 3802 Gold 12' width (3.66 m) 0.6" W x 1.0" L ASTM E 648 Class 1 (Glue Down) ASTM E 662 Less than 450 AATCC-134 Under 3.5 KV Lifetime Limited Wear Warranty Lifetime Limited Edge Ravel, Zippering, Delamination and Dimensional Stability Warranty Lifetime Limited Colorfastness to Light Warranty 10 Year Limited Stain Resistance Warranty
		and Dimensional Stability Warranty Lifetime Limited Colorfastness to Light Warranty		ants	and Dimensional Stability Warranty Lifetime Limited Colorfastness to Light Warranty
	Warranties	•	I	Warranties	•
	Static Propensity	AATCC-134 Under 3.5 KV		Static Propensity	AATCC-134 Under 3.5 KV
	Flammability	ASTM E 648 Class 1 (Glue Down)		Flammability	ASTM E 648 Class 1 (Glue Down)
		, ,			
	NSF 140	Gold		NSF 140	Gold
	Soil Release Technology Primary Backing Secondary Backing	Mohawk Protection Plus Soil Woven Polypropylene Weldlok® Plus		Soil Release Technology Primary Backing Secondary Backing	Mohawk Protection Plus Soil Woven Polypropylene Weldlok® Plus
ROADLOOM	Collection	Define Broadloom Denote / 2B125 Tufted Level Multi-Colored Patterned Loop 1/12" (47.00 rows per 10 cm) 69% Solution Dyed / 31% Yarn Dyed Colorstrand® Nylon	ROADLOOM	Collection	Define Broadloom Construe / 2B126 Tufted Level Multi-Colored Patterned Loop 1/12" (47.00 rows per 10 cm) 68% Solution Dyed / 32% Yarn Dyed Colorstrand® Nylon

гθΙ	Brand	Aladdin Commercial
	Collection	Define Broadloom
BROADLOOM	Style Name / Number	Classify / 2B127
0	Construction	Tufted
γD	Surface Appearance	Level Multi-Colored Patterned Loop
30/	Gauge	1/12" (47.00 rows per 10 cm)
ВЕ	Dye Method	67% Solution Dyed / 33% Yarn Dyed
	Fiber Type	Colorstrand® Nylon
	Stain Release Technology	Mohawk Protection Plus Stain
	Soil Release Technology	Mohawk Protection Plus Soil
	Primary Backing	Woven Polypropylene
	Secondary Backing	Weldlok® Plus
	Indoor Air Quality	
	NSF 140	
	Size	, ,
	Pattern Repeat	
	Flammability	ASTM E 648 Class 1 (Glue Down)
	Smoke Density	
	Static Propensity	AATCC-134 Under 3.5 KV
	Warranties	Lifetime Limited Wear Warranty
		Lifetime Limited Static Protection Warranty
		Lifetime Limited Edge Ravel, Zippering, Delamination
		and Dimensional Stability Warranty
		Lifetime Limited Colorfastness to Light Warranty
		10 Year Limited Stain Resistance Warranty
		10 Year Limited Colorfastness to Atmospheric Contaminants



Mohawk Industries, Inc. warrants its adhesives for the life of the original installation only when a Mohawk Industries style (product) is installed. Mohawk's floor preparation procedures must be followed to ensure that the substrate has been prepared properly. Failure to use Mohawk Industries adhesives or to follow Mohawk's floor preparation procedures will void all lifetime adhesive warranties. Please contact your local Sales Representative for installation guidelines.

Mohawk is providing this architect folder for the purpose of promoting our commercial business. Color may vary from dye lot to dye lot. Substitution of material may be made due to improved technology, supply limitations or other factors. The performance of this product is not affected by such variations. We recommend the use of chair pads on all commercial installations.

 $For current and complete specifications \ please \ call \ tech \ support \ at \ 888-387-9881 \ or \ visit \ www.mohawkflooring.com \ I \ 800.233.4490$ 





