





## Specifications

_	
	Sty
≥	Co
0	Su
7	Ga
ADL	De
חם	Dy
۵	Fib
	So
	Pri
	Se
	Inc

[A | Brand ..... ...... Aladdin Commercial yle Name / Number...... Front & Center / 2B212 nstruction ...... Tufted rface Appearance ...... Texture Patterned Loop uge...... 1/10 (39.37 rows per 10cm) ..... 4,881 ve Method...... 100% Solution Dyed oer Type ...... Envirostrand™ SD PET il Release Technology....... Mohawk Protection Plus Soil imary Backing ...... Woven Polypropylene condary Backing ...... Weldlok® ndoor Air Quality...... Green Label Plus Certified # 0350 NSF 140 ...... Gold Size...... 12' width (3.66 m) Pattern Repeat ...... 0.4" W x 0.8" L Flammability ...... ASTM E 648 Class 1 (Glue Down) Smoke Density ...... ASTM E 662 Less than 450 Static Propensity...... AATCC-134 Under 3.5 KV Warranties...... 10 Year Limited Wear Warranty 10 Year Limited Static Protection Warranty 10 Year Limited Edge Ravel, Zippering, Delamination, and Dimensional Stability Warranty 10 Year Limited Colorfastness to Light Warranty 10 Year Limited Stain Resistance Warranty 10 Year Limited Colorfastness to Atmospheric Contaminants



Mohawk Industries, Inc. warrants its adhesives for the life of the original installation only when a Mohawk Industries style (product) is installed. Mohawk's floor preparation procedures must be followed to ensure that the substrate has been prepared properly. Failure to use Mohawk Industries adhesives or to follow Mohawk's floor preparation procedures will void all lifetime adhesive warranties. Please contact your local Sales Representative for installation guidelines.

Mohawk is providing this architect folder for the purpose of promoting our commercial business. Color may vary from dye lot to dye lot. Substitution of material may be made due to improved technology, supply limitations or other factors. The performance of this product is not affected by such variations. We recommend the use of chair pads on all commercial installations.

