












## Barrali

Featuring wider plank design and unique visuals from textile to natural wood, Barrali from Aladdin Commercial offers performance LVT fit for a variety of commercial environments.

## Features:

- M-Force™ 1 Enhanced Urethane Finish
- 20 mil wear layer
- No polish maintenance reduces occupied costs
- 2.5 mil overall thickness

- 8" x 52" nominal plank size
- Limited 10 Year Commercial Warranty
- Limited 25 Year Residential Warranty
- Made in America
- FloorScore Certified









659 Hebe



718 Cane







751 Bay 888 Nova 929 Dove

# UltraSet® Matrix

Aladdin Commercial continues its dedication to sustainable solutions with UltraSet® Matrix, the next generation in carpet tile backing. Using advanced materials and patent pending engineering, UltraSet® Matrix lowers environmental impact without sacrificing performance. UltraSet® Matrix simplifies floor preparation and installation, greatly reduces sub-floor moisture concerns, and is easier to ship and handle.


## **PERFORMANCE**

CARPET TILE

- Provides permanent dimensional stability
- Tiles are impervious to moisture damage from spills and water extraction cleaning
- Up to Lifetime Limited Carpet Tile Warranty for: Wear, Static Protection, Edge Raveling/Zippering, Delamination, Dimensional Stability\*
- Seamless transitions between carpet and hard surface flooring with 2.5 mm LVT resilient products

#### **INSTALLATION**

- Simplifies complex floor preparation with no need to encapsulate old adhesives\*\*\*
- · Greatly reduces sub-floor moisture concerns and saves money on mitigation
- Worry free installation with no visible moisture present using our Flexlok Tab System
- Superior construction offers reliability for the life of your installation



#### **SUSTAINABILITY**

- UltraSet® Matrix is manufactured using less energy than other carpet tile products
- Polyolefin backing contains no plasticizers
- Contains a minimum of 40% preconsumer recycled content based on total product weight\*\*
- CRI Green Label Plus certified
- Declare Red List Free
- Recyclable
- · Able to ship more per box resulting in a lower environmental impact from transportation
- \*Lifetime or 10 Year Limited Warranty varies by fiber type, please see specifications for details
  \*\*Recycled content claim third party verified by UL (Underwriters Laboratory)
- \*\*\*Consult Mohawk Installation Instructions for any applicable restrictions

# Specifications

] [	Brand	Aladdin Commercial		Brand	Aladdin Commercial
	Collection	Primary Effect Collection		Collection	Primary Effect Collection
:	Style Name / Number	Surface Stitch / 2B175	TIE	Style Name / Number	Pattern Perspective / 2B176
-	Construction	Tufted		Construction	Tufted
3	Surface Appearance	Textured Patterned Loop	ET	Surface Appearance	Textured Patterned Loop
:	Gauge	1/12" (47.00 rows per 10 cm)	ARP	Gauge	1/12" (47.00 rows per 10 cm)
5	Density	6,585	CA	Density	7,297
	Dye Method	100% Solution Dyed		Dye Method	100% Solution Dyed
	Fiber Type	Colorstrand® SD Nylon		Fiber Type	Colorstrand® SD Nylon
	Stain Release Technology	Mohawk Protection Plus Stain		Stain Release Technology	Mohawk Protection Plus Stain
	Soil Release Technology	Mohawk Protection Plus Soil		Soil Release Technology	Mohawk Protection Plus Soil
	Primary Backing	Non Woven Synthetic		Primary Backing	Non Woven Synthetic
	Secondary Backing	UltraSet® Matrix		Secondary Backing	UltraSet® Matrix
	Indoor Air Quality	Green Label Plus Certified # 100055		Indoor Air Quality	Green Label Plus Certified # 100055
	Size	24" x 24" (.6096 m x .6096 m)		Size	24" x 24" (.6096 m x .6096 m)
	Yds./Ctn	10.66		Yds./Ctn	10.66
	Installation Method	Monolithic / Vertical Ashlar / Brick Ashlar /		Installation Method	Monolithic / Vertical Ashlar / Brick Ashlar /
		Quarter Turn / Multi-Directional			Quarter Turn / Multi-Directional
	Flammability	ASTM E 648 Class 1 (Glue Down)		Flammability	ASTM E 648 Class 1 (Glue Down)
	Smoke Density	ASTM E 662 Less than 450		Smoke Density	ASTM E 662 Less than 450
	Static Propensity	AATCC-134 Under 3.5 KV		Static Propensity	AATCC-134 Under 3.5 KV
	Warranties	Lifetime Limited Wear Warranty		Warranties	Lifetime Limited Wear Warranty
		Lifetime Limited Static Protection Warranty			Lifetime Limited Static Protection Warranty
	Lifetime Limited Edge Ravel, Zippering, Delamination,			1,	Lifetime Limited Edge Ravel, Zippering, Delamination,
		and Dimensional Stability Warranty			and Dimensional Stability Warranty
		Lifetime Limited Colorfastness to Light Warranty			Lifetime Limited Colorfastness to Light Warranty
	10 Year Limited Stain Resistance Warranty				10 Year Limited Stain Resistance Warranty
	10 Year Limited Colorfastness to Atmospheric Contaminants			minants	10 Year Limited Colorfastness to Atmospheric Contaminants

#### Installation Instructions

	Mo	nolit	hic	Quarter Turn	Brick Ashlar	Vertical Ashlar	Multi-Directional
	1	1	1	↑ → ↑	†     †     †       †     †     †	<u>†</u> † †	↑ ↓ ←
	1	1	1	$\rightarrow$ $\uparrow$ $\rightarrow$			→ ↑ →
	1	†	1	↑	†   †   †	† † †	←   →   ↓



Mohawk Industries, Inc. warrants its adhesives for the life of the original installation only when a Mohawk Industries style (product) is installed. Mohawk's floor preparation procedures must be followed to ensure that the substrate has been prepared properly. Failure to use Mohawk Industries adhesives or to follow Mohawk's floor preparation procedures will void all lifetime adhesive warranties. Please contact your local Sales Representative for installation guidelines

Mohawk is providing this architect folder for the purpose of promoting our commercial business. Color may vary from dye lot to dye lot. Substitution of material may be made due to improved technology, supply limitations or other factors. The performance of this product is not affected by such variations. We recommend the use of chair pads on all commercial installations.

For current and complete specifications please call tech support at 888-387-9881 or visit www.AladdinCommercial.com I 800.233.4490





