





92 Stony Oak Grey
Cover: 47 Sannita Neutral

Specifications

LVT	Brand	Aladdin Commercial
	Style Name / Number	Oaklawn Park / AH099
	Product Type	Flexible LVT
	Overall Gauge	4.2mm
	Wear Layer	12 mil
	Finish	Enhanced Urethane Finish
	Colors Available	10
	Size	12" x 24" (colors 02, 47) 6" x 48" (colors 03, 95A) 6" x 36" (colors 232, 444, 92) 8" x 48" (colors 43, 94, 930)
	Packaging	
	SF/ Carton	12" x 24" = 20 sq ft/ctn 6" x 48" = 20 sq ft/ctn 6" x 36" = 21 sq ft/ctn 8" x 48" = 18.69 sq ft/ctn
	Cartons/Pallet	60 cartons/pallet
	Weight/ Carton	12" x 24" = 27.21 lbs/ctn 6" x 48" = 29.60 lbs/ctn 6" x 36" = 31.04 lbs/ctn 8" x 48" = 27.82 lbs/ctn
	Classification	ASTM F1700 - Class III, Type A - Smooth, Type B - Embossed
	Squareness	ASTM F 2421 - Passes - $\pm 0.10"$ max
	Size and Tolerance	Tile ASTM F2055; Plank ASTM F2421 - Passes - $\pm 0.016"$ /linear foot
	Thickness	ASTM F386 - Passes - as specified $\pm 0.005"$
	Flexibility	ASTM F137 - Passes - 1" mandrel
	Dimensional Stability	ASTM F2199 - Passes - 0.020"/linear foot max
	Static Load	ASTM F970 - Passes, modified at 1500 psi
	Residual Indentation	ASTM F1914 - Passes - Average less than 8% maximum single reading 10%
	Slip Resistance	ASTM C1028 - Passes Wet: ≥ 0.5
	Resistance to Chemicals	ASTM F925 - Passes - No more than a slight change
	Resistance to Light	ASTM F1515 - Passes - $\Delta E < 8$
	Resistance to Heat Flux	ASTM E649 - Class 1 (> 0.45 W/cm ²)
	Smoke Density	ASTM E662 Part A - Less than 450
	Installation Method	Clic (Locking)
	Recommended Adhesive	M95.0 Resilient Flooring Adhesive, M99 Resilient Flooring Adhesive, or M700 Pressure Sensitive Adhesive
	Optional Underlayment	Mohawk ActiveSound - Clic
	Certification	FloorScore® Certified
	Warranty	10 Year Limited Light Commercial Warranty 25 Year Limited Residential Warranty



Mohawk Industries, Inc. warrants its adhesives for the life of the original installation only when a Mohawk Industries style (product) is installed. Mohawk’s floor preparation procedures must be followed to ensure that the substrate has been prepared properly. Failure to use Mohawk Industries adhesives or to follow Mohawk’s floor preparation procedures will void all lifetime adhesive warranties. Please contact your local Sales Representative for installation guidelines.

Mohawk is providing this architect folder for the purpose of promoting our commercial business. Color may vary from dye lot to dye lot. Substitution of material may be made due to improved technology, supply limitations or other factors. The performance of this product is not affected by such variations. We recommend the use of chair pads on all commercial installations.

For current and complete specifications please call tech support at 888-387-9881 or visit www.AladdinCommercial.com I 800.233.4490

