

Sohana II






























Sohana II

Bringing sophistication with a modern-rustic twist, Sohana II was inspired by nature-influenced artwork and hues. The wide array of color and design allows for easy coordination in a multitude of aesthetics.

Features:

- 2 mm overall thickness
 - 6” x 48” wood planks
 - 6 mil or 12 mil wear layer
 - Commercial Urethane Finish
- FloorScore® Certified
 - Limited 5 Year Light Commercial Warranty (6 mil)
 - Limited 10 Year Light Commercial Warranty (12 mil)
 - Limited 25 Year Residential Warranty



Specifications

LVT	Brand.....	Aladdin Commercial
	Style Name / Number	Sohana II 6 mil / AH031
	Product Type	Luxury Vinyl Tile
	Overall Gauge.....	2mm
	Wear Layer	6 mil (0.15mm)
	Finish.....	Commercial Urethane Finish
	Colors Available.....	14
	Size.....	6”x 48” (152.4mm x 1,219.2mm)
	Packaging SF/CTN.....	54 sf/ctn; 54 ctns/pallet (2,592 sf); 35.43 lbs./ctn
	Classification	ASTM F1700 - Class III, Type A - Smooth, Type B - Embossed
	Squareness.....	ASTM F2421 - Passes - ±0.10” max
	Size and Tolerance	Tile ASTM F2055; Plank ASTM F2421 Passes - ±0.16”/linear foot
	Thickness.....	ASTM F386 - Passes - As specified ±0.005 in.
	Flexibility	ASTM F137 - Passes - 1” mandrel
	Dimensional Stability	ASTM F2199 - Passes - 0.020”/linear foot max
	Static Load Limit	ASTM F970 - Passes, modified at 1500 psi
	Residual Indentation	ASTM F1914 - Passes - Average less than 8%, maximum single reading 10%
	Slip Resistance.....	ASTM C1028 - Passes - Wet: greater than/equal to 0.5
	Resistance to Chemicals	ASTM F925 - Passes - No more than a slight change in surface dulling, surface attack or staining
	Resistance to Light.....	ASTM F1515 - Passes - ΔE < 8
	Resistance to Heat Flux.....	ASTM E649 - Class 1 (>0.45 W/cm²)
	Smoke Density.....	ASTM E662 Part A - Less than 450
	Installation	Glue Down
	Adhesive.....	M95.0 Resilient Flooring Adhesive, MS160 Spray or M700 Pressure Sensitive Adhesive
	Optional Underlayment	Mohawk AccuSound™
	Certification.....	FloorScore® Certified
	Warranty	Limited 5 Year Light Commercial Warranty Limited 25 Year Residential Warranty

LVT	Brand.....	Aladdin Commercial
	Style Name / Number	Sohana II 12 mil / AH032
	Product Type	Luxury Vinyl Tile
	Overall Gauge.....	2mm
	Wear Layer	12 mil (0.30mm)
	Finish.....	Commercial Urethane Finish
	Colors Available.....	14
	Size.....	6”x 48” (152.4mm x 1,219.2mm)
	Packaging SF/CTN.....	54 sf/ctn; 54 ctns/pallet (2,592 sf); 35.43 lbs./ctn
	Classification	ASTM F1700 - Class III, Type A - Smooth, Type B - Embossed
	Squareness.....	ASTM F2421 - Passes - ±0.10” max
	Size and Tolerance	Tile ASTM F2055; Plank ASTM F2421 Passes - ±0.16”/linear foot
	Thickness.....	ASTM F386 - Passes - As specified ±0.005 in.
	Flexibility	ASTM F137 - Passes - 1” mandrel
	Dimensional Stability	ASTM F2199 - Passes - 0.020”/linear foot max
	Static Load Limit	ASTM F970 - Passes, modified at 1500 psi
	Residual Indentation	ASTM F1914 - Passes - Average less than 8%, maximum single reading 10%
	Slip Resistance.....	ASTM C1028 - Passes - Wet: greater than/equal to 0.5
	Resistance to Chemicals	ASTM F925 - Passes - No more than a slight change in surface dulling, surface attack or staining
	Resistance to Light.....	ASTM F1515 - Passes - ΔE < 8
	Resistance to Heat Flux.....	ASTM E649 - Class 1 (>0.45 W/cm²)
	Smoke Density.....	ASTM E662 Part A - Less than 450
	Installation	Glue Down
	Adhesive.....	M95.0 Resilient Flooring Adhesive, MS160 Spray or M700 Pressure Sensitive Adhesive
	Optional Underlayment	Mohawk AccuSound™
	Certification.....	FloorScore® Certified
	Warranty	Limited 10 Year Light Commercial Warranty Limited 25 Year Residential Warranty

Aladdin
COMMERCIAL

Mohawk Industries, Inc. warrants its adhesives for the life of the original installation only when a Mohawk Industries style (product) is installed. Mohawk’s floor preparation procedures must be followed to ensure that the substrate has been prepared properly. Failure to use Mohawk Industries adhesives or to follow Mohawk’s floor preparation procedures will void all lifetime adhesive warranties. Please contact your local Sales Representative for installation guidelines.

Mohawk is providing this architect folder for the purpose of promoting our commercial business. Color may vary from dye lot to dye lot. Substitution of material may be made due to improved technology, supply limitations or other factors. The performance of this product is not affected by such variations. We recommend the use of chair pads on all commercial installations.

For current and complete specifications please call tech support at 888-387-9881 or visit www.AladdinCommercial.com I 800.233.4490



Berklee
002



Brennex
003



Laken
012



Myla
016



Remi
072



Wylla
096



Rowan
124



River
136



Reed
167



Russet
460



Carob
584



Aphrodite
852



Dover
932



Pinales
983

