

INFUZE SEAM SEALER

INSTALLATION INSTRUCTIONS AND
MATERIAL SAFETY DATA SHEET



160 South Industrial Blvd.
Calhoun, GA. 30701
Dalton, GA 30721

www.mohawkflooring.com

Technical Services Department
508 East Morris St.
Dalton, GA 30721
888.387.9881

DESCRIPTION:

A non-flammable 100% solids, one component, cross linking, modified silane polymer based seam sealer formulated for the seaming of vinyl backed sheet goods.

APPLICATION

1. Prepare vinyl according to Aladdin Commercial installation instructions.
2. Apply a bead (approximately 1/8") along the entire edge of the commercial sheet vinyl. Apply seam sealer to only one side of the vinyl to be seamed.
3. Complete the seam by tucking both sections of the sheet vinyl together while the adhesive is still wet.
4. Roll seam with a hand roller to remove excess seam sealer.
5. Always recap seam sealer between applications.
6. Remove any excess seam sealer by wiping with a clean dry cloth, followed by a cloth dampened with mineral spirits.
7. Dried sealer may be removed with approved adhesive remover/stripper
8. Protect the seam area for a minimum of 6 hours to allow seam to fully cure.

PHYSICAL PROPERTIES

Base:	Modified Silane Polymer Blend
Appearance:	White, smooth, creamy, easy to apply
Shelf Life:	One year in unopened container at 70oF (21.10o C)
Coverage:	Approximately 140 to 150 linear feet/5 oz. tube
Other Features:	Waterproof when cured. VOC compliant, non-flammable, freeze-thaw stable to 10° F (-12.22° C)
Clean Up:	Use Mineral Spirits, approved Adhesive Remover/Stripper.

CAUTION

DO NOT take internally. If swallowed, DO NOT induce vomiting. Call a physician immediately.
KEEP OUT OF REACH OF CHILDREN.

WARRANTY INFORMATION: This product is manufactured according to exacting quality control standards and warranted to be free from manufacturing defects. Defective material called to our attention within one year of manufacture will be replaced. No guarantee, expressed or implied is made regarding the performance of this product since the manner and conditions of application are beyond our control. For complete warranty information, call IVC at 888-387-9881.

508 E. Morris Street Dalton, GA 30721 | 888.387.9881| mohawkflooring.com

Aladdin Commercial Infuze Seam Sealer MATERIAL SAFETY DATA SHEET

SECTION I HAZARDOUS INGREDIENTS

None per OSHA Regulation: 29 CFR 1910.1200

SARA Title III Section 313 Chemicals: None

NFPA HMIS

H = 1

F = 0

R = 0

SECTION II PHYSICAL DATA

Boiling Point: No data.

LBS/GAL: 8.6 - 9.2

Evaporation Rate/Vapor Density: Low.

Vapor Pressure: Low.

Percent Volatile: 0 (by weight), 100 solids

Odor: Mild.

Color: White.

SECTION III FIRE AND EXPLOSION HAZARD DATA

DOT Category: Not regulated

Flash Point: N/A

LEL: N/A

Extinguishing Media: Water spray, CO₂, foam, dry chemical. Unusual Fire and Explosion Hazards: None

Special Fire Fighting Procedures: Use self contained breathing apparatus.

SECTION IV HEALTH HAZARD DATA

Symptoms of Over Exposure

Inhalation: May cause slight irritation to the upper respiratory tract.

Eyes: Vapor may cause irritation.

Skin: May cause slight irritation.

Ingestion: Not a likely route of entry under proper handling conditions. May cause vomiting.

Symptoms may be same as inhalation.

First Aid Procedures:

Eyes: Flush with water.

Skin: Wash with soap and water.

Inhalation: Remove to fresh air if needed. Administer oxygen if necessary.

SECTION V REACTIVITY DATA

Stability: Stable

Conditions to avoid: Keep away from extreme temperature conditions.

Incompatibility/Materials to avoid: Metal salts may coagulate the product.

Hazardous decomposition products: Oxides of carbon, water, and organic compounds of unknown structure.

Hazardous polymerization: Will not occur.

SECTION VI SPILL OR LEAK PROCEDURES

Steps to Be Taken if Material is Spilled: Keep out of sewer systems to prevent blockage due to polymer deposits. Use absorbent materials to collect and/or scrape up excess and place into closed DOT approved containers for disposal.

Waste Disposal: Abide by all State, Federal and local regulations.

SECTION VII SPECIAL PROTECTION INFORMATION

Respiratory protection: NIOSH respirator if needed
Ventilation: Local exhaust. Do not use closed air-circulating system. Open windows and doors if necessary.

Protective gloves: Chemical resistant gloves, apron, coveralls, and boots as necessary to prevent contact.
Eyes: Chemical goggles or face shield.

Other protective equipment: None

SECTION VIII SPECIAL PRECAUTIONS

Precaution for Handling and Storing: Do not puncture, protect from freezing and excessive heat. **KEEP OUT OF REACH OF CHILDREN**