

Mohawk Seam Sealer

NuBroadlok™ Solvent-Free Carpet Seam Sealer is recommended for seaming polypropylene, jute, urethane, latex unitary carpet and woven backed and vinyl backed edges. It prevents unraveling and/or delaminating of carpet backings and yarns. NuBroadlok™ Solvent Free Carpet Seam Sealer can be used for direct stick and conventional stretch-in installations and is resistant to mildew, fungus and professional carpet cleaning.

NU BROADLOCK™ SOLVENT FREE CARPET SEAM SEALER IS NOT RECOMMENDED FOR SEAMING SHEET GOODS.

Features:

- **CRI Green Label Plus Approved**
- **Non-Flammable**
- **Water Cleanup**
- **Low Odor / Odorless When Dry**
- **For Most Carpet Backings**

Preparation & Application:

- NuBroadlok™ Solvent Free Carpet Seam Sealer is NOT freeze thaw stable. Do not allow the adhesive to freeze.
- NuBroadlok™ Solvent Free Carpet Seam Sealer and substrate must be at least 65°F (18°C) or higher.
- Prepare and cut the carpet edges according to Mohawk's recommendations.

Direct Glue Down Installation:

Apply a 1/8" bead of adhesive to only one side of the carpet along the backing and where the face yarns enter the backing (not the cushion). Smooth out any excess adhesive being careful not to get any adhesive on the carpet nap.

Close the seam by joining both sides of the carpet while the adhesive is still wet and can be transferred easily. If the carpet separates, realign both sections with a knee kicker to closely join the edges.

Stretch-in Installation:

Apply 1/8" bead of adhesive to BOTH sides of the carpet along the backing and where the face yarns enter the backing (not to cushion). Smooth out any excess adhesive being careful not to get any adhesive on the carpet nap.

As an edge sealer, allow the adhesive on both edges of the carpet to become dry to the touch before joining the seam.

Clean Up:

Do not allow adhesive to dry on carpet nap. Adhesive must be removed while it is still wet. Use a non-flammable cleaner to remove any traces of sealer left on the face of the yarn that can eventually attract dirt.

Coverage:

NuBroadlok™ Solvent Free Carpet Seam Sealer 8 ounce (246.5 ML) container covers approximately 85-100 linear feet.

Warranty:

Buyer assumes all risk of use, handling and storage of product not in strict accordance with label directions. No express warranties are given. Any implied warranty of merchantability of fitness for particular use is limited to one year from date of purchase. Liability for an incidental or consequential damage or loss is specifically excluded at all times. If used for other than professional purposes, any implied warranty of merchantability or fitness for a particular use is excluded.

First Aid:

In case of eye contact, flush with water for 15 minutes, call physician if irritation occurs. Skin contact – wash with soap and water. If swallowed, do not induce vomiting, call a physician immediately. For more detailed information, refer to the product material safety data sheet (MSDS).

KEEP OUT OF REACH OF CHILDREN.

Protect from freezing.

Technical Services: 1-888-387-9881, option 2