

AccuSound™

Polypropylene Acoustical Underlayment for use with Glue Down Luxury Vinyl Tile

The ultimate in double glue down applications, or glue down with loose lay floating LVT, AccuSound™ underlayment provides excellent sound reduction and moisture protection under luxury vinyl flooring. This underlayment is ideal for multi-level installations.

- Specifically designed to secure the flooring to the pad and the pad to the substrate
- Dense foam design fights against mold and mildew
- Non-toxic, odorless
- Moisture and vapor resistant construction
- Install AccuSound™ with Mohawk M95.0, M700 or MS160 spray adhesive



AccuSound™ Specifications	
Material Thickness (EN 822)	1 mm
Dimensions/SF per roll	5 ft x 40 ft / 200 sq. ft.
Punctual Conformability PC (CEN/TS 16354)	Approx. 1 mm = 0.04 in
Impact Insulation Class (ASTM E492)*	IIC 70
Sound Transmission Class (ASTM E90)*	STC 66
Compression Set @ 50% Deflection	29.5%
Compression Deflection 25%	25.9 psi
Foam Color	Black
Weight per Roll	13.1 lbs
Tensile	273 psi
Tear	44.4 lb/in
Rolls per Pallet	70

* Test results over 6" slab and drop ceiling.
Test results without drop ceiling available by contacting Mohawk Tech Services 800.833.6954

Mohawk MS160 Resilient Spray Adhesive is a water-based adhesive recommended for installations of resilient floor coverings. It is particularly convenient as it can be used in occupied buildings which greatly reduces the handling and application requirements associated with conventional adhesives. Mohawk MS160 Adhesive demonstrates highly aggressive grab and shear strength, and has outstanding water and plasticizer resistance.

- Non-flammable, no solvents or hazardous chemicals
- "Zero" (calculated) VOC, Very Low Odor
- Outstanding water resistance when dry
- Passes Air Quality Standards per California Section 01350
- CRI Green Label Plus approved/SCS FloorScore® Certified
- Moisture tolerance - 93% RH