



Hospitality Nylon Modular Tile on EcoFlex NXT Durkan

Final Assembly: Glasgow, Virginia, USA

Life Expectancy: 15 Year(s)

End of Life Options: Take Back Program (ReCover), Recyclable

Ingredients:

Coating: Calcium Carbonate; Polypropylene Copolymer; Calcium carbonate; Butadiene Acrylate; Ethylene Malyceic Anhydride Copolymer; Propylene Homopolymer; Tackifier; Ammonium Lauryl Sulfate; Black Pigment; Sodium Polyacrylate Thickner; **Yarn:** Nylon 6; Nylon 66; Titanium dioxide; **Topical:** 2-Propenoic acid, 2-methyl-, butyl ester, polymer with butyl 2-propenoate and methyl 2-methyl-2-propenoate; Bisphenol-s Phenolsulfonic acid resin; Phosphoric acid, dodecyl ester, potassium salt; **Dyes:** Blue Colorant; Blue Colorant; Red Colorant; Yellow Colorant; **Primary:** Polyester; Polypropylene; **Scrim:** Fiberglass Mat; Modified Acrylic Copolymer

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|-----------------------------|
| ☒ LBC Red List Free | % Disclosed: 100% at 100ppm |
| ☐ LBC Red List Approved | VOC Content: Not Applicable |
| ☐ Declared | |

I-10 Interior Performance: CDPH Standard Method v1.1-2010

I-14 Responsible Sourcing: Not Applicable

DRK-0002

EXP. 01 SEP 2021

Original Issue Date: 2014