



Hospitality Nylon Modular Tile on EcoFlex ICT Durkan

Final Assembly: Glasgow, Virginia, USA

Life Expectancy: 15 Year(s)

End of Life Options: Take Back Program (ReCover)

Ingredients:

Coating: Ashes (residues); Calcium Carbonate; Ammonium Lauryl Sulfate; Calcium Oxide; Sodium Polyacrylate; Soy Lecithin; **Yarn:** Nylon 6; Nylon 66; Titanium dioxide; **Backing:** Chloroethene Polymer With Methyl 2-Propenoate; Di(2-ethylhexyl) terephthalate; 2-Propenoic acid, 2-methyl-, methyl ester, polymer with 1,3-butadiene; Polyvinyl chloride; **Primary:** Polyester; Polyamide; Polypropylene; **Topical:** 2-Propenoic acid, 2-methyl-, butyl ester, polymer with butyl 2-propenoate and methyl 2-methyl-2-propenoate; Bisphenol-s Phenolsulfonic acid resin; Phosphoric acid, dodecyl ester, potassium salt; **Dye:** Various Colorants; **Scrim:** Fiberglass Mat; Modified Acrylic Copolymer

Living Building Challenge Criteria:

I-13 Red List:

- | | |
|--|-----------------------------|
| ☐ LBC Red List Free | % Disclosed: 100% at 100ppm |
| ☐ LBC Red List Approved | VOC Content: Not Applicable |
| ☒ Declared | |

I-10 Interior Performance: CDPH Standard Method v1.1-2010

I-14 Responsible Sourcing: Not Applicable

DRK-0003

EXP. 01 SEP 2021

Original Issue Date: 2014