

Hospitality Precision Dye Injected Carpet on EcoFlex NXT Air (PDI/Synthesis) Durkan

Final Assembly: Glasgow, Virginia, USA

Life Expectancy: 15 Year(s)

End of Life Options: Salvageable/Reusable in its Entirety, Take

Back Program (ReCover), Recyclable (100%)

Ingredients:

Coating: Recycled Calcium Carbonate; 2-Propenoic acid, 2-methyl-, methyl ester, polymer with 1,3-butadiene; Polypropylene Copolymer; Propylene Homopolymer; Ammonium Lauryl Sulfate; Black Pigment; Ethylene Malyceic Anhydride Copolymer; Polyolefin; Sodium Polyacrylate; 2,5-Furandione, polymer with ethene and 1-propene; Tris(2,4-di-tert-butylphenyl) phosphite; Yarn: Nylon 6; Nylon 66; Titanium dioxide; Cushion: Polyester; PDI Dyes: Blue Colorant; Red Colorant; Yellow Colorant; Primary: Propylene Homopolymer; Nylon 6; Polyester; Scrim: Glass, oxide, chemicals; Modified Acrylic Copolymer; Topical: 2-Propenoic acid, 2-methyl-, butyl ester, polymer with butyl 2-propenoate and methyl 2- methl-2-propenoate; Benzenesulfonic acid, hydroxy-, monosodium salt, polymer with formaldehyde and 4,4'-sulfonylbis[phenol]; Phosphoric acid, dodecyl ester, potassium salt

Living Building Challenge Criteria: Compliant

I-13 Red List:

□ Declared

■ LBC Red List Free

% Disclosed: 100% at 100ppm VOC Content: Not Applicable

☐ LBC Red List Approved

I-10 Interior Performance: CDPH Standard Method v1.1-2010

I-14 Responsible Sourcing: Not Applicable

DRK-0011 EXP. 01 JUL 2021 Original Issue Date: 2019