



D

Tesserae

Romulus Chariot Race Pilus





Romulus 957 Hypnós (Brick Ashlar Installation)  
Cover: Romulus 957 Hypnós with Secoya 989 Calaveras (Brick Ashlar Installation)



DURKAN



Chariot Race 957 Hypnos (Brick Ashlar Installation)





Pilus 957 Hypnos (Brick Ashlar Installation)



DURKAN



Ambulation 957 Hypnos (Brick Ashlar Installation)  
Custom Pattern, minimum of 500 sq./yds.





Bricolage 957 Hypnos (Brick Ashlar Installation)  
Custom Pattern, minimum of 500 sq./yds.



DURKAN



Castilly 957 Hypnos (Brick Ashlar Installation)  
Custom Pattern, minimum of 500 sq./yds.





Legatus 957 Hypnos (Brick Ashlar Installation)  
Custom Pattern, minimum of 500 sq./yds.



DURKAN



Oculus 957 Hypnos (Brick Ashlar Installation)  
Custom Pattern, minimum of 500 sq./yds.





Olive Grove 957 Hypnos (Brick Ashlar Installation)  
Custom Pattern, minimum of 500 sq./yds.



DURKAN



Indira 957 Hypnos (Brick Ashlar Installation)  
Custom Pattern, minimum of 500 sq./yds.





Tanith 957 Hypnos (Brick Ashlar Installation)  
Custom Pattern, minimum of 500 sq./yds.



DURKAN




Vitaceae 957 Hypnos (Brick Ashlar Installation)  
Custom Pattern, minimum of 500 sq./yds.



# Hot & Heavy SECOYA & BOLDER

Bold, contemporary aesthetics of hardwood and polished concrete gain new versatility in the Hot & Heavy Collection of loose-lay luxury vinyl tile. Secoya explores warm and cool tones of richly grained hardwood visuals in a substantial 9" x 59" plank. Bolder grounds spaces with deep taupes and grays in a polished concrete visual and hefty 36" x 36" tile. The oversize format of both styles provides striking visual impact as well as rapid installation in large, open-concept spaces.



- Mottled concrete and hardwood visuals create stunning and unique installations
- Oversized 36" x 36" tiles and 9"x 59" planks install over large areas quickly
- 5mm overall thickness and 20 mil commercial wear layer for superior durability
- M-Force™ Ultra finish for stain and wear resistance
- Twice as thick as traditional LVT for seamless transition with Mohawk Group carpet tiles
- Non-skid backing keeps tiles in place





Specifications

Romulus MD001  
Chariot Race MD002  
Pilus MD003

DESIGN

Size	24" x 24" (.6096m x .6096m)
Surface Appearance	Textured Patterned Cut and Loop
Fiber Type	Duracolor® Tricor Premium Nylon
Dye Method	Solution Dyed
Installation Methods	Monolithic / Quarter Turn / Brick Ashlar / Vertical Ashlar / Multi-Directional
Colors Available	15

PERFORMANCE

Construction	Tufted
Gauge	1/12" (47.00 rows per 10cm)
Stain Release Technology	Permanent, Built into the Fiber
GSA Stain Release Technology	Passes
Soil Release Technology	EcoSentry Soil Protection
Backing Material	EcoFlex NXT
Flammability	ASTM E 648 - Class 1 (Glue Down)
Smoke Density	ASTM E 662 - Less than 450
Static Propensity	AATCC - 134 Under 3.5 KV


SUSTAINABILITY

Certification	Declare Red List Free
Indoor Air Quality	Green Label Plus Certified #1171
NSF 140	Gold

SERVICE

Warranties	Lifetime Limited Carpet Tile Warranty, Lifetime Limited Duracolor Stain Warranty, Lifetime Static
------------	---

Installation Instructions:



Mohawk Group warrants its adhesives for the life of the original installation only when a Mohawk Group style (product) is installed. Mohawk's floor preparation procedures must be followed to ensure that the substrate has been prepared properly. Failure to use Mohawk Group adhesives or to follow Mohawk's floor preparation procedures will void all lifetime adhesive warranties. Please contact your local Sales Representative for installation guidelines.

**These patterns contain inherent characteristics which may result in pattern run off and/or pattern appearance variations at the seams or tile edges (darker or lighter pattern lines). These characteristics are inherent in the patterns and are not manufacturing defects. Consideration to these characteristics should be given when selecting an installation method.**

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to prevent premature or accelerated wear. Walk-off tiles from the Tuff Stuff II Collection are recommended at entryways to reduce soiling.

Duracolor by Mohawk Stain Resistant System passes AATCC Test Method 175 combined with pre-abrasion meeting GSA requirements for stain resistance. Under GSA requirements stain resistant carpets must score no less than 8.0 (10.0 is best) on the AATCC Red 40 Stain Scale. Carpet samples must first be exposed to 100 revolutions of the

Taber abrader (1,000-gram weight per H-18 wheel) and then the abraded area must be stain tested using AATCC tested using AATCC test method 175.

Mohawk Group is providing this architect folder for the purpose of promoting our commercial business. This folder and its samples shall remain the property of Mohawk Group. Color may vary from dye lot to dye lot. Substitution of material may be made due to improved technology, supply limitations or other factors. The performance of this product is not affected by such variations.

For current and complete specifications please visit [durkan.com](http://durkan.com)



